
PRODUCT DATA SHEET

NEW ILIADE

Recessed for outdoor use. Body and base in aluminum with acrylic diffuser. Transverse rotation of the body of 360 µs and longitudinal of 90 µs. Power supply integrated in the base. Complete with formwork.



PRODUCT CODE: NILI - F - 12 - WW / - NW - AG



https://www.lucecontrocorrente.com/prodotti/134-new-iliade

DELIVERY TIMES: 4/6 Weeks from order confirmation

PHYSICAL CHARACTERISTICS

Assembly	Recessed for floor
Finishing	Grey anodized
Hardware	Stainless
Gaskets	N.B.R.
Hollow press	Nickel-plated brass
Degree of protection	IP65
Body	Anticorodal Aluminium
Environment of use	Esterni
Operating temperature	-10°/+40°

ELECTRICAL CHARACTERISTICS

Lamp holder	-
Power supply	Built-in
Tension	230Vac
HZ	50-60Hz
Max Watt	12W
Emission angle	12° | 24° | 35° | 50° | 60°
Diffuser	Clear acrylic
Reflector	-

LIGHT SOURCE CHARACTERISTICS


Light emission	1500 lm
Type of Source	Led COB
Color temperature	3000° | 4000° K
Optical characteristics	12° | 24° | 35° | 50° | 60°

REGISTERED OFFICE - HOLBARG SRL
Via W. Gnutti 64/B
46043 Castiglione delle Stiviere (Mantova) Italy

ADMINISTRATIVE HEADQUARTERS - LUCECONTROCORRENTE
Via Necropoli Romana 20
Cortine di Nave (Brescia) Italy

030 558 2457 | www.lucecontrocorrente.com | info@lucecontrocorrente.com

TECHNICAL DRAWING



REGISTERED OFFICE - HOLBARG SRL
Via W. Gnutti 64/B
46043 Castiglione delle Stiviere (Mantova) Italy

ADMINISTRATIVE HEADQUARTERS - LUCECONTROCORRENTE
Via Necropoli Romana 20
Cortine di Nave (Brescia) Italy

030 558 2457 | www.lucecontrocorrente.com | info@lucecontrocorrente.com