
PRODUCT DATA SHEET

P7

Interior lamp in the suspension and wall versions.
Extruded aluminium lamp body, anti-glare longitudinal lines diffuser in metalicrate.
Steel suspension cables with clutch block.



PRODUCT CODE: P7 - 1000 / - 1500 / - 2000 - W / - S - 15 / - 23 / - 30 - SWW / - WW - AG / - AL



htthttps://www.lucecontrocorrente.com/prodotti/176-p2

DELIVERY TIMES: 4/6 Weeks from order confirmation

PHYSICAL CHARACTERISTICS

Assembly	Wall | Suspension
Finishing	Grey anodized | Polished Aluminium
Hardware	Stainless
Gaskets	-
Hollow press	-
Degree of protection	IP40
Body	Anticorodal Aluminium
Environment of use	Indoors
Operating temperature	-10°/+40°

ELECTRICAL CHARACTERISTICS

Lamp holder	-
Power supply	Built-in | External
Tension	24 | 230 Vdc
HZ	50-60Hz
Max Watt	7,5 | 15 | 30 | 45 W
Emission angle	180°
Diffuser	Metalicrate longitudinal lines
Reflector	-

LIGHT SOURCE CHARACTERISTICS


Light emission	1760 | 1900 | 2460 | 2850 | 3520 | 3800 lm
Type of Source	Strip Led
Color temperature	2700° | 3000° K
Optical characteristics	Diffused Light


REGISTERED OFFICE - HOLBARG SRL
Via W. Gnutti 64/B
46043 Castiglione delle Stiviere (Mantova) Italy

ADMINISTRATIVE HEADQUARTERS - LUCECONTROCORRENTE
Via Necropoli Romana 20
Cortine di Nave (Brescia) Italy

030 558 2457 | www.lucecontrocorrente.com | info@lucecontrocorrente.com

TECHNICAL DRAWING





REGISTERED OFFICE - HOLBARG SRL
Via W. Gnutti 64/B
46043 Castiglione delle Stiviere (Mantova) Italy

ADMINISTRATIVE HEADQUARTERS - LUCECONTROCORRENTE
Via Necropoli Romana 20
Cortine di Nave (Brescia) Italy

030 558 2457 | www.lucecontrocorrente.com | info@lucecontrocorrente.com